

BVFC 12/12

GENERAL DATA



BOX FAN WITH FORWARD IMPELLER AND BELT TRASMISSION - 400°C/2h

MANUFACTURING FEATURES:

- Fans in thermal and soundproofing cabinets.
- Double inlet forward curved impeller.
- Transmission set outside the airstream including the belts protection grid.

• Standard asynchronous squirrel-cage motor with IP-55 protection and Class F insulation. Manufactured with standard voltages: 230/400V 50Hz in three phase motors up to 4kW and 400/690V 50Hz for higher powers. 2 speed motors 400V 50Hz

APPLICATIONS:

Designed for inline installation, indoor or outdoor assembly, they are suitable for: • Smoke emergency exhaust with motor outside the hazardous area.


- Industrial and professional kitchen hoods.
- Maximum working temperature: carried air: 110°C, ambient: 60°C.

UNDER REQUEST:

- 60Hz fans and special voltages.
- Vertical discharge.
- 2 Speed

Official homologation by the European laboratory APPLUS according to EN 12101-3:2015 Certification Nr: 0370-CPR-0723

PERFORMANCE CURVE






1


v10.28.0



TECHNICAL DATA




DIMENSIONS



Dimensions (mm)									
А	951	В	678	С	970,5	D	400	E	345
F	30	G	851	Н	573	I	29	К	1147
L	1067	М	891.5	Ν	60	0	72,5	Р	260

WIRING DIAGRAM



ACCESSORIES



METALLIC GRAVITY SHUTTER FOR CABINET FANS. CERTIFIED 400ºC/2H PI 33/33 (12/12) REF: 970330100 INLET/OUTLET ROUND COVER TIAC 4 (OUT) REF: 960001354



2





INLET/OUTLET ROUND COVER TIAC 9 (IN)

REF: 960001359



OUTDOOR FLANGE WITH BIRD GUARD VIS OUT 12 REF: 960000052

FREQUENCY SPEED CONTROLLER

ANTI-VIBRATION RUBBER BLOCK

ANTI-VIBRATION



INLET BLIND COVER TCA 14 REF: A-960001124



ANTI-VIBRATION

RECTANGULAR-CIRCULAR FLANGE BAC 4 (OUT 12/12) REF: 960002954

SFC (GENERIC)

AVR (GENERIC)



RECTANGULAR-CIRCULAR FLANGE BAC 9 (IN BVFC 12/12) REF: 960002959




SAFETY SWITCH INT (GENERIC)



ANTI-VIBRATION SPRING BLOCK AVS (GENERIC)

SPARE PARTS



Qty Code Model BEARING COLL.EXC. NP25 C3-120ºC 712919125 2 x2 6 242302112 SHAFT BVFC12/12 x1 IMPELLER BV-BVFC 12/12 7 R-252309381 x1 BOX (WITHOUT MOTOR NOR TRANSMISSION) BVFC 12/12 8 R-242308493 x1



This report data could change without any previous advise