

COURSALIS 1000 E (509610000B)

Exclusive arch design, light and superfine High performance and low sound level

Metallic housing with paint finish in white colour

GENERAL DATA

HIGH PERFORMANCE AIR CURTAIN FOR TERTIARY WITH HEATING





Metallic impeller Includes external control by remote control Designed for horizontal mural installation With operating indicator LED (ambient or heating, air velocity and stop motion) Mounting brackets on wall Reach up to 3m. The indicated weight does not include the packaging (± 2Kg.)

APPLICATION

380V 50Hz motor

Equipped with electrical coil

Tertiary sector:

- Airports.
- Schools
- Malls.
- Stores.
- Supermarkets.
- Train stations.
- Hotels. Restaurants
- Pubs
- Offices.
- Banks
- Gas stations
- Logistics centers.
- Industries, food industries.
- Hospitals, clinics, health centers.
- Veterinary clinics.
- Refrigerated warehouses.

TECHNICAL DATA

Fan							
RPM	1400	Approx. weight	17.6 kg	Max. Flow	1100 m³/h		
Motor	_	_					
Power	4,4 kW	RPM	1400	l max. (400V)	11,637 A	Approx. weight	0 kg





DIMENSIONS



imensions ((mm)				
А	1150	F	195	G	220

WIRING DIAGRAM



ACCESSORIES



SAFETY SWITCH INT 25 3P A REF: INT253PA



2